


UniXact® Series-C

Precision Automated Dispense Solutions

Increase productivity with an automation solution designed to fit your dispensing needs.



Configurable for dispensing one and two-component chemistries, with flexibility to adapt when materials or substrates change



Become more profitable with:

- More up time
- Faster cycles times
- Reduced waste and rework

Maintain high quality through:

- Consistent, high-precision dispensing
- Real-time process monitoring
- Quality Graco components

Full support of a global leader with 90 years of expertise in precision dispensing technology

- Made in the U.S.A.
- Local service, support and training



Graco UniXact C300

Graco UniXact® Precision Dispense Solutions

Graco Dispense Valves

- Precise one and two-component dispensing
- Reliable, repeatable fluid flow control
- Simple valve design means easy maintenance
- Compatible with a variety of materials and viscosities

Motion Platform

OPERATION

- Intuitive touch-screen operator controls
- Real-time process monitoring with data download
- Light curtain, guarding, and safety interlock system
- 3D contour dispense capability (3 axis interpolation)

PROGRAMMING

- Proprietary Graco software designed to dispense
- DXF upload for fast programming
- Off-line programming feature
- Store hundreds of programs onboard

HARDWARE

- Speed: 200mm/s point-to-point; 100mm/s dispense
- Repeatability: +/- 0.01mm (0.0004in)
- Servo drive motors for X,Y,Z movement
- Ball screw drives with linear guide bearings
- Heavy duty payload for handling dispense equipment - up to 22kg

OPTIONS

- Customizable mounting plates and nests
- Dual Y-Slide option for increased productivity
- Automatic needle locating and cleaning features
- Part-in-place detection sensor
- Vision system for programming and part placement correction

C300 Model

Overall Dimensions:

Width: 940 mm (37 in)
Height: 1905 mm (75 in)
Depth: 1045 mm (41 in)




C500 Model

Width: 1200 mm (47 in)
Height: 2000 mm (79 in)
Depth: 1200 mm (47 in)

Maximum Dispense Area*:

X: 290 mm (11.42 in)	X: 540 mm (21.26 in)
Y: 330 mm (12.99 in)	Y: 515 mm (20.28 in)
Z: 70 mm (2.75 in)	Z: 130 mm (5.12 in)

* Dispense area is dependent on valve type and chosen accessories.
Contact Graco for further information.



For more information, contact Logan La
Cock at sales@limitsa.co.za, 017 634 4852

© 2019 Graco Inc. 349475 Rev. E 10/19 All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.